



SAFEPRO

SFP6000

Upper: Full Grain Crazy Horse

Lining: Air mesh, with WR Membrane waterproof sock

Outsole: new formula DESMA, PU+Rubber, Full Black

WIDE TOE Fiber Glass Composite toe

Kevlar Midsole

EH18KV

Insole: High elastic Sponge Memory

#1: 6 TEST INTERTEK: ASTM EH IC PR (COMPLETE BOOTS)

#3: 2 TEST INTERTEK: EN ISO 20345 SRC (OUTSOLES ONLY) Test in SFP2000

#4: 1 TEST INTERTEK: WATERPROOF MEMBRANE (MEMBRANE ONLY)

#5: 1 TEST INTERTEK: PATOGEN MEMBRANE (MEMBRANE ONLY)



EURO SIZE	LABEL SIZE	WIDTH
40	7 - 7.5	STANDARD
41	8 - 8.5	STANDARD
42	9 - 9.5	STANDARD
43	10 - 10.5	STANDARD
44	11 - 11.5	STANDARD

GENUINE PERFORMANCE FOOTWEAR

Slip Resistant | Oil resistant | Dielectric Metal Free
 Meets or Complies with ASTM F2413-18.
 Impact Resistance (I): ASTM F2413-18.
 Compression Resistance (C): ASTM F2413-18.
 Electrical Hazard Protection (EH): ASTM F2413-18.
 ASTM Puncture Resistance (PR)
 Full Premium PR Midsole
 High Test Composite Toe
 Full Breathable Construction.
 Full Grain Leather
 Waterproof Membrane
 EN ISO 20345:2022 SR SLIP RESISTANCE



SAFETY TOE CAP ANTI-SLIP SHOCK ABSORPTION OIL RESISTANT PETROL AND CHEMICAL RESISTANT PR MIDSOLE

Manufacturer: LV International, Miami FL, 33166